



Estimates of Navy Ship Traffic in Puget Sound and Adjacent Coastal Waters

Jonathon Mintz Ronald Filadelfo

March 22, 2004





- Specific questions we'll look at:
 - What fraction of coastal ship traffic do Navy ships account for?
 - How do radiated noise levels of Navy ships compare to those of other ships?
- Outline
 - Offshore transit area
 - → Vessel tracks
 - → Ship-hours
 - → Radiated noise
 - Puget Sound
 - → Ship hours
 - → Radiated noise
 - Summary







Overview

DRAFT


Merchant/Fishing (left) and US Navy (right)








Took a closer look at a "transit-only" area






Ship hours in 2002 (in transit area)






Vessel radiated noise

DRAFT






1/3 octave band at 70 hz




Puget Sound






Overall ship hours 2002 (in Puget Sound)





Vessel Radiated Noise, Puget SoundRAFT



1/3 octave band at 70 hz



- "On average", Navy ships account for a small fraction of the coastal ship traffic
- Fundamental differences in distributions
 - Navy traffic is high patchy, in space and time
 - Commercial traffic is more uniform
- Major Navy activities (exercise, BG movements) produce vessel densities roughly ½ of the commercial background
- "On average", Navy ships account for a small fraction of the ship-generated low frequency broadband acoustic energy in the coastal ocean
 - Even large concentrations of Navy ships emit less acoustic energy than the commercial background
 - Scoping-level calculations!
- Data presented here does not include recreational vessel traffic
 - Data on recreational vessels extremely limited
 - → Radiated noise data virtually non-existent







Back-up information



Appendix: Sample radiated noise calculations


	Number	70 HZ	erg/cm^2/sec	watts per	total
TYPE	Present	signature	per ship	ship	watts
CGO	12.76	173 ^a	133.08	1.40	17.84
BLK	6.47	173 ^a	133.08	1.40	9.05
TUG	9.70	166 ^d	26.55	0.28	2.71
TKR	4.98	167 ^b	33.43	0.35	1.75
FSH	1.22	157 ^c	3.34	0.04	0.04
RES	0.73	166 ^d	26.55	0.28	0.20
SVC	0.84	166 ^d	26.55	0.28	0.24
PAS	17.94	166 ^d	26.55	0.28	5.00
SPA	0.00	166 ^d	26.55	0.28	0.00
FAC	0.07	166 ^d	26.55	0.28	0.02
MIS	0.74	166 ^d	26.55	0.28	0.21
TRN	0.03	166 ^d	26.55	0.28	0.01
ICE	0.33	166 ^d	26.55	0.28	0.09
REF	0.04	166 ^d	26.55	0.28	0.01
YMT	0.03	166 ^d	26.55	0.28	0.01

- a. Urick 1983, figure 10.15; Used "freighter" curve, and made frequency and bandwidth corrections
- b. Urick 1983, figure 10.15; Extrapolated speed up from 14 to 15 kt; made frequency correction by extrapolating the curve for "normal speeds and loading" down to 70 hz by fitting a line with EXCEL; added 12 db to convert to band level
- c. Richardson 1995, figure 6.5a; used curve for trawler; Added 1 db to convert to ref. distance of 1 yd
- d. Richardson 1995, figure 6.7; Used levels for "Support and Supply" ships (refers to ships of roughly 55-85 m); Took average, in intensity units, of 2 of the 3 ships shown (3rd looked to be outlier); added 35 db to convert from ref distance of 55 yd





Breakout of Navy traffic (in transit area)





US Navy breakdown (in Puget Sound)

